

Handy Gloss Meter

PG-1 / PG-1M



**Compact, light-weight, battery-operated and simple operation.
It conforms to the gloss standards of JIS, ISO, ASTM and DIN.
You can measure three angles (20°, 60° and 85°) instantaneously
only by this instrument (PG-1M).**

Features

1. Functions such as storing, saving, inputting, referencing, and statistical calculation of the measured data are provided as a standard.
2. No warming-up time is required and it has one-touch operation to set a gloss reference value, average the measured values, and save your data.
3. This model automatically covers a wide range of 0 to 2,000 gloss.
4. Remote control is possible using an RS-232C interface and a gloss meter can be used as a sensor.

Specifications

Dimensions	L 150mm x D 49mm x H 80mm
Weight	Approx. 420g (without batteries)
Power supply	Alkaline dry battery 9V x 1
Power consumption	825mW (maximum)
Light source	Tungsten lamp 5V 125mA
Measuring items	GU, ΔGU
Measuring range	0 to 2,000 Gloss Unit (GU), with automatic range selection
Measuring area	20° : 10.0mm x 10.6mm 75° : 7.0mm x 27.0mm 45° : 10.0mm x 14.1mm 85° : 10.0mm x 40.1mm 60° : 10.0mm x 20.0mm

Measuring angle	<ul style="list-style-type: none"> • PG-1 : 20°, 45°, 60°, 75°, 85° (to be selected) • PG-1M : 3 angles of 20°, 60°, 85°
Related standards	JIS Z 8741, ISO 2818, ISO 7668
Measurement accuracy	<ul style="list-style-type: none"> • ±1GU (reproducibility : 0.0 to 199.9) • ±10GU (reproducibility : 200 to 2,000)
Option	<ul style="list-style-type: none"> • RS-232C interface cable • Printer, etc.



NIPPON
Advanced Technology in Color and Brightness.
DENSHOKU

© NIPPON DENSHOKU INDUSTRIES CO., LTD.

HEAD SALES DEPT. SENGOKU HASEGAWA BLDG. 4-45-17 SENGOKU, BUNKYO-KU, TOKYO 112-0011 JAPAN
PHONE: 81-3-3946-4392 ■ FAX: 81-3-3946-1690 ■ URL <http://www.nippondenshoku.co.jp/>